


Suno™ Hotelcard switch Cat. No(s): 7 21X 75




### 1. USE

Hotel room lightning controls mechanism.
Supplied with support frame cover plates.
Mechanisms supplied with protection cover.
To be equipped with plates one or several gangs.
Flush-mounting or surface-mounting.
Screw or claw fixing.

### 2. RANGE

| Description               | White     | lvory     | Aluminium    | Black        |
|---------------------------|-----------|-----------|--------------|--------------|
|                           | RAL9003   | RAL1013   | RAL9023      | RAL9017      |
|                           | Polygloss | Polygloss | Matt painted | Matt Painted |
| MECHANICAL KEYCARD SWITCH | 7 211 75  | 7 212 75  | 7 213 75     | 7 214 75     |

#### 3. DIMENSIONS (mm)



| References | Α    | В    | С    | D    |
|------------|------|------|------|------|
| 7 21X 75   | 72,9 | 72,9 | 51,9 | 24,6 |

## 4. CONNECTION

Type of terminals: with screws Therminal capacity: 2 x 2.5 mm<sup>2</sup> Stripping length (mm): 12 mm Flexible or rigid cables compatible

## **5. TECHNICAL CHARACTERISTICS**

#### ■ 5.1 Mechanical characteristics

Protection against solid bodies and liquids: IP 20 Protection against impact: IK 04

### ■ 5.2 Material characteristics

Material:

- Mechanism housing: PC
- Cover plates: ABS
- Halogen free
- UV resistant
- Claws: steel

Material of the support:

- ABS+ steel
- Halogen free

#### Self-extinguishing:

 $850^{\circ}\text{C}/30 \text{ s}$  for insulating components holding live parts in place  $650^{\circ}\text{C}/30 \text{ s}$  for other insulating components

#### ■ 5.3 Electrical characteristics

Voltage: 250 V~ Current: 10 AX

for Cat. Nos 7 520 02/41 - 7 521 02 - 7 522 02 - 7 523 02 - 7 563 22

Max. power for self-ballasted lamps: 100 W Current: 16 AX for Cat. No 7 520 27 Max. power for self-ballasted lamps: 200 W

Frequency: 50/60 Hz

#### ■ 5.4 Climate characteristics

Storage and usage temperature: -  $5^{\circ}$ C to +  $35^{\circ}$ C

# 6. MAINTENANCE

Surface cleaning with a cloth.

Do not use: acetone, tar remover, trichloroethylene.

Maintenance with the following products: Hexane (EN 60669-1), Methylated spirit, Soapy water, Diluted ammonia, Bleach diluted to 10%, Window-cleaning products, Pre-Impregnated-wipes.

Caution: Always test before using other special cleaning products.

# 7. STANDARDS AND APPROVALS

Compliant with installation and manufacturing standards. See e. catalogue.